






EASY OPERATION. REASONABLE PRICE. HIGH PRINT QUALITY.

Designed for small office and home office, the G&G L2050DW 3 in 1 printer guarantees the high efficiency in print, copy and scan. The separate drum unit and toner cartridge bring into full play in terms of energy conservation and environmental protection. The compact and lightweight design enable you to maximize your desktop and working space.



DESIGNED FOR SOHO

-  Print/Copy/Scan 3 in 1
-  Excellent Monochrome Output
-  Automatic Duplex Printing
-  One-step Driver Installation
-  Separate Drum Unit and Toner



L2050DW

KEY SPECIFICATIONS



L2050DW

3 in 1 ADF

MODEL

PRINT

Print speed	33ppm(A4) / 35ppm(Letter)
First print out time	≤ 8.2s
Maximum monthly duty cycle	30000 pages
Recommended monthly volume	750 to 2500 pages
Print resolution (maximum dpi)	Max 1200x1200 dpi
Print languages	PCL5e / PCL6 / PS / PDF
Processor speed	525MHz
Memory, standard	256MB
Duplex printing	Automatic
Network / Wi-Fi	Yes

PAPER HANDLING

Paper input capacity	250 pages
Multipurpose tray	1 page
Paper output capacity	150 pages(A4/70g)
Media types	Plain / Thick / Thin / Transparency / Cardstock / Label
Media sizes	A4, A5, JIS B5, ISO B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6 Yougata4, Postcard, Younaga3, Nagagata3, Yougata2
Media weights	Standard tray: 60-105g/m ² Multipurpose tray: 60-200g/m ²

COPY

Copy speed (letter, black)	33ppm(A4) / 35ppm(Letter)
First copy out time	Flatbed: less than 10s ADF: less than 11s
Copy resolution (max. dpi)	Max 600×600 dpi
Maximum copy pages	99 pages
Copy reduce / enlarge settings	25%~400%
Copy special features	ID copy, Receipt copy, N-up copy, Clone copy / poster copy / Manual Duplex Copy / collated copy

SCAN

Scanner type	Flatbed & ADF
ADF capacity	50 pages
Scan speed (maximum)	24 ppm(A4) / 25 ppm(Letter)
Scan size (maximum)	Flatbed : 216×297mm / ADF: 216 x 356 mm
Scan resolution	Flatbed : Max 1200×1200dpi / ADF : Max 600×600dpi
Color scanning	Yes
Scan destinations	Scan to PC / E-mail / FTP / thumb drive

GENERAL

Dimensions(W×D×H)	415 x 365 x 350mm
Weight(without cartridge)	11.29kg
Operating environment	Recommended temperature: 10-32°C / Humidity range: 20% Humidity range: 20%-80% 80%
Power consumption	Printing: 550W / Ready: less than 50W / Sleep: less than 2W
Noise level	Printing: 52dB(A) / Copy: 54dB(A) / Scan: 52dB(A) / Standby: 30dB(A)
Operating system compatibility	Microsoft Windows Server 2003 / Server 2008 / Server 2012 / XP / Vista / Win7 / Win8 / Win8.1 / Win10(32/64 Bit) Mac OS 10.7-10.15 Linux: Ubuntu 12.04/14.04/16.04/18.04/20.04(32/64 Bit)
Standard ports	Hi-Speed USB 2.0 / Net: IEEE 802.3 10/100Base-Tx / WiFi: IEEE 802.11b/g/n

CONSUMABLE *

Consumable type	Toner Cartridge & Drum Unit
Starter cartridge(1)	TL1500(1500 Pages)
Starter drum(2)	DL12000(12000 Pages)
Cartridge model and yield(1)	TL1500 / TL3000 / TL6000(1500 / 3000 / 6000 Pages)
Standard drum(2)	DL12000(12000 Pages)

Note: (1) Toner capacity is based on ISO 19752.

(2) Drum unit lifetime is based on 3 average letter/A4-size pages per print job and 5% coverage, actual lifetime affected by different printing habits and printing environment.